

RAXSAT300

SAT Cable reel up to 300m + 45m

In combination with the SAT crawler RX140SAT II and an automatic cable reel RAX300 / RAX500 the SAT cable reel provides the opportunity to inspect laterals from the main sewer.

Technical Data - RAXSAT300

Drive	motor-driven
Camera cable length	max. 300 m
Push rod length	45 m
Push rod diameter	11 mm
Meter counter	yes (integrated)
Deflection pulley	yes
Voltage	230VAC / 115VAC
Frequency	50Hz / 60Hz
Power	approx. 500W
Protection class	IPX4
Ambient temperature range	0°C to 40°C
Storage temperature range	-20°C to 70°C
Dimensions (BxHxL)	370 x 760 x 900 mm
Weight	approx. 110 kg*

RAXSAT300 compatible with:

Control panel DCX5000	yes
Control panel VC500	no
Cable reels RAX300, RAX500	yes
Cable reels RMX200, RMB100	no
Crawler RX140SAT II	yes
Crawlers RX95, RX130, RX400, RX140SAT	no
Cameras PTP50, AC40	yes
Cameras PTP70 II, RCX90	no



Features

- Up to 300m of extremely robust camera cable for a long range of the SAT crawler in the main sewer
- 45m extremely robust but still flexible push rod for long inspection ranges of the SAT camera in laterals
- SLC winding concept ensures optimum winding performance
- LCD touch display for meter counter display and operation of the SAT drum in set-up mode
- Easy to service because of a pluggable connector between camera cable and push rod.
- Optionally available as EX version
- Optional available cable wiper to catch dirty water and impurities

*with 300m camera cable and 45m push rod